

Product	P4 indoor full color LED module
Module size	256*128mm
Pixel density	62500dots/m²
LED lamp	SMD2121
Module resolution	64*32
Module consumption	28W/pcs
Viewing distance	4-30m
Max power consumption	900W/m²
Standard cabinet size	768*768mm
Drive mode	1/16scan
Brightness	≥1200cd/m²
HUB mode	HUB75
Drive IC	FM5020/SM16107
Frame frequency	≧60Hz/s
Refresh rate	≧360Hz/s
MTTF	>5000 hours
Life time	>100,000 hours
Defect rate	<0.0001
Video signal input	RF, S-video, RGB, RGBHV, YUV, YC, composition

Temperature range	Storage	-20 to 65℃
	Working	-20 to 50℃
Gray scale/color	4096 grades for R ,G and B	
Display	≥16.7M colors	
Working voltage	110/220V AC	
Viewing angle	Horizontal	140°
	Vertical	140°
Display content	videos, pictures and graphics	
Operating humidity	10-90%	
Storage humidity	10-90%	
Continue working time	24 hours	
Control mode	synchronization/asynchronization	
Warranty	2 years	
Module weight	0.25KG/PCS	
Delivery time	7-15 days	

High value purchase fashion

Using high-quality red, green and blue three kinds of chip package in a table lamp beads, the surface of the lamp beads according to a certain spacing evenly attached to the front of the circuit board and welding fixed, the back of the circuit board with the drive and control electronic components Device, and then use the plastic package to secure and protect the finished circuit board, which is the indoor P2LED display basic unit.

Ultra-wide viewing angle, bring you a new experience

Surface lamp beads their own perspective, and then use high-precision equipment and advanced technology production, unique anti-electromagnetic processing, distributed scanning technology, modular design, the reliability and stability of higher. So that the horizontal and vertical viewing angle is broader, stable performance, wide broadcast content.

The consistency of the filling product is good

Using the industry's top technology irrigation, irrigation flat, dust and moisture, to ensure product consistency.

Super mute

Super quiet fan design, high heat dissipation, no noise.

